

R2-IBT-200-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1700	402 / 0.19	494 / 0.27	626 / 0.48	719 / 0.62	786 / 0.72	841 / 0.79	890 / 0.86	935 / 0.91	978 / 0.97
2100	497 / 0.35	565 / 0.44	660 / 0.62	768 / 0.88	850 / 1.09	913 / 1.23	966 / 1.35	1013 / 1.45	1055 / 1.53
2500	591 / 0.59	646 / 0.68	713 / 0.84	801 / 1.10	894 / 1.42	970 / 1.69	1031 / 1.90	1083 / 2.07	1129 / 2.21
2900	686 / 0.92	733 / 1.02	785 / 1.17	849 / 1.38	927 / 1.70	1008 / 2.07	1080 / 2.42	1141 / 2.71	1192 / 2.95
3300	780 / 1.35	821 / 1.47	865 / 1.61	914 / 1.80	973 / 2.07	1041 / 2.43	1114 / 2.85	1182 / 3.27	1242 / 3.64
3700	875 / 1.91	911 / 2.04	949 / 2.19	990 / 2.37	1036 / 2.60	1089 / 2.91	1149 / 3.30	1214 / 3.76	1278 / 4.24
4100	969 / 2.59	1002 / 2.74	1036 / 2.90	1071 / 3.08	1110 / 3.29	1152 / 3.57	1200 / 3.90	1253 / 4.32	1310 / 4.80
4500	1064 / 3.43	1094 / 3.59	1124 / 3.75	1156 / 3.94	1189 / 4.15	1225 / 4.41	1264 / 4.70		
4900	1158 / 4.43	1186 / 4.60	1214 / 4.78	1242 / 4.97					

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.