

R2-IBT-300-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2400	370 / 0.26	462 / 0.34	577 / 0.51	675 / 0.71	762 / 0.94	842 / 1.17	917 / 1.40	987 / 1.63	1052 / 1.86
2800	432 / 0.41	502 / 0.50	605 / 0.65	698 / 0.87	780 / 1.11	857 / 1.37	928 / 1.64	995 / 1.91	1059 / 2.18
3200	494 / 0.61	550 / 0.70	636 / 0.85	724 / 1.07	804 / 1.32	876 / 1.60	944 / 1.89	1009 / 2.19	1070 / 2.50
3600	556 / 0.87	603 / 0.97	673 / 1.11	753 / 1.32	830 / 1.57	900 / 1.86	965 / 2.17	1027 / 2.50	1086 / 2.83
4000	617 / 1.19	658 / 1.30	715 / 1.44	786 / 1.63	858 / 1.89	926 / 2.18	989 / 2.50	1049 / 2.84	1106 / 3.19
4400	679 / 1.58	715 / 1.70	762 / 1.84	823 / 2.03	889 / 2.27	954 / 2.56	1016 / 2.88	1074 / 3.23	1129 / 3.60
4800	741 / 2.05	772 / 2.18	814 / 2.33	865 / 2.51	923 / 2.74	984 / 3.02	1044 / 3.34	1100 / 3.69	1154 / 4.07
5200	802 / 2.61	831 / 2.75	867 / 2.90	911 / 3.08	962 / 3.30	1017 / 3.57	1074 / 3.88	1128 / 4.23	1181 / 4.61
5600	864 / 3.26	890 / 3.41	922 / 3.57	960 / 3.75	1005 / 3.97	1054 / 4.22	1106 / 4.52	1158 / 4.86	
6000	926 / 4.00	950 / 4.17	979 / 4.34	1012 / 4.53	1051 / 4.74	1095 / 4.99			

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.