

R2-IBT-800-400-400-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4000	690 / 1.31	751 / 1.57	822 / 1.84	887 / 2.10	945 / 2.36	1000 / 2.62	1052 / 2.89	1104 / 3.18	1155 / 3.48
4200	725 / 1.52	781 / 1.79	850 / 2.07	914 / 2.35	971 / 2.62	1024 / 2.89	1074 / 3.17	1124 / 3.46	1173 / 3.77
4400	760 / 1.75	812 / 2.03	877 / 2.32	940 / 2.62	996 / 2.90	1048 / 3.18	1097 / 3.47	1145 / 3.77	1192 / 4.08
4600	794 / 2.00	844 / 2.29	906 / 2.60	967 / 2.91	1022 / 3.20	1073 / 3.50	1121 / 3.80	1168 / 4.11	1213 / 4.42
4800	828 / 2.27	876 / 2.57	934 / 2.90	994 / 3.22	1048 / 3.53	1098 / 3.84	1146 / 4.15	1191 / 4.46	1235 / 4.79
5000	863 / 2.57	908 / 2.88	963 / 3.21	1021 / 3.55	1075 / 3.88	1124 / 4.20	1171 / 4.52	1215 / 4.85	
5200	897 / 2.89	940 / 3.21	993 / 3.56	1049 / 3.91	1101 / 4.25	1150 / 4.59	1196 / 4.92		
5400	932 / 3.23	972 / 3.56	1023 / 3.93	1077 / 4.30	1128 / 4.65	1176 / 5.00			
5600	967 / 3.61	1005 / 3.95	1053 / 4.32	1105 / 4.70					
5800	1001 / 4.01	1038 / 4.36	1083 / 4.74						
6000	1036 / 4.44	1071 / 4.80							

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.