

**R4-IBT-1600-400-400-400-400-920**

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
9000	555 / 3.23	596 / 3.58	637 / 4.01	685 / 4.53	738 / 5.15	785 / 5.76	824 / 6.33	857 / 6.87	886 / 7.37
9500	586 / 3.79	625 / 4.17	663 / 4.60	707 / 5.13	756 / 5.75	804 / 6.41	845 / 7.04	880 / 7.62	910 / 8.18
10000	617 / 4.42	654 / 4.82	690 / 5.26	730 / 5.79	775 / 6.41	822 / 7.10	865 / 7.79	902 / 8.43	934 / 9.04
10500	648 / 5.12	683 / 5.53	717 / 5.99	754 / 6.52	796 / 7.14	841 / 7.85	884 / 8.58	923 / 9.28	956 / 9.95
11000	679 / 5.89	713 / 6.31	745 / 6.78	779 / 7.32	818 / 7.94	860 / 8.66	903 / 9.42	942 / 10.17	977 / 10.90
11500	709 / 6.73	742 / 7.17	773 / 7.66	805 / 8.20	841 / 8.82	880 / 9.53	921 / 10.31	961 / 11.11	997 / 11.90
12000	740 / 7.65	772 / 8.11	801 / 8.61	832 / 9.15	865 / 9.78	901 / 10.49	940 / 11.28	979 / 12.11	
12500	771 / 8.64	801 / 9.12	830 / 9.63	859 / 10.20	890 / 10.82	923 / 11.53	960 / 12.32	998 / 13.17	
13000	802 / 9.72	831 / 10.22	859 / 10.75	886 / 11.32	915 / 11.95	947 / 12.66	981 / 13.44		

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.